

A++

R32

-25 ~ 32°C
-15 ~ 48°C

ARIES

- WiFi control
- LED display
- Timer
- Night mode
- Self cleaning
- Selfdiagnosis
- High temperature sterilization at 57°C
- Energy saving
- Silver-ion filter
- Dehumidification
- Silent mode
- Large air flow range - up to 15 m
- Chassis electric heater function

MODEL	CAPACITY (W)		ENERGY CLASS SEER /SCOP	DIMENSION H/W/D (mm)
	COOLING	HEATING		
AZI-WK25XA/I	2700	3000	6,2 / 4,0 A++ / A+	296 / 761 / 199
AZI-WK25XA/O	(600 - 3800)	(800 - 4200)		530 / 705 / 280
AZI-WK35XA/I	3500	3800	6,1 / 4,0 A++ / A+	296 / 761 / 199
AZI-WK35XA/O	(800 - 4100)	(1000 - 4200)		530 / 705 / 280
AZI-WK50XA/I	5300	5400	6,8 / 4,0 A++ / A+	315 / 960 / 221
AZI-WK50XA/O	(1300 - 5900)	(1300 - 6000)		555 / 785 / 300
AZI-WK70XA/I	7300	7300	6,5/ 4,0 A++ / A+	328 / 1089 / 227
AZI-WK70XA/O	(1800 - 7400)	(1800 - 8000)		700 / 900 / 350

PIPING CONNECTION	CAPACITY (kW)			
	2,7	3,5	5,3	7,3
Max. piping height [m]	15	15	20	25
Max. piping lenght [m]	25	25	30	50
Outer diameter of liquid pipe [mm]	6,35	6,35	6,35	6,35
Outer diameter of gas pipe [mm]	9,52	9,52	12,7	15,9

