NEW 2026

VEZURI V

MONOBLOC TS

AIR TO WATER HEAT PUMP

R290

-25 ~ 35°C
-15 ~ 48°C

DHW
-25 ~ 45°C

WATER OUTLET
20 ~ 80°C
5 ~ 25°C

- All-in-one solution for heating, cooling, and domestic hot water up to 80°C
- Uses eco-friendly R290 refrigerant (GWP 3.0) for high efficiency and low environmental impact
- High-efficiency patented deaerator for enhanced safety and reliability
- Built-in WiFi control for remote operation
- Low noise operation down to 40 dB(A)
- Modern LCD display with built-in temperature sensor and USB interface.
- Zone control to meet different temeprature requirements.

MODEL	CAPACITY (W)		EER A35/W18 A35/W7	COP A7/W35 A7/W45
	COOLING A35/W18 A35/W7	HEATING A7/W35 A7/W55		
Power Source: 1Ph / 220-240 V / 50 Hz				
AZI-CQ6.0Pd/NpG4-E	6 200 / 6 100	6 200 / 6 100	5,2 / 3,2	5,0 / 3,9
AZI-CQ8.0Pd/NpG4-E	8 300 / 7 500	8 400 / 8 200	5,2 / 3,2	5,0 / 3,9
AZI-CQ10Pd/NpG4-E	10 000 / 8 900	10 000 / 10 000	4,8 / 3,05	4,75 / 3,7
AZI-CQ12Pd/NpG4-E	12 000 / 11 600	12 000 / 12 000	4,6 / 3,15	4,95 / 3,8
AZI-CQ14Pd/NpG4-E	14 000 / 12 800	14 000 / 14 000	4,3 / 2,95	4,7 / 3,7
AZI-CQ16Pd/NpG4-E	15 500 / 14 000	15 500 / 15 000	4,4 / 2,85	4,7 / 3,75
Power Source: 3Ph / 380 - 415 V / 50 Hz				
AZI-CQ8.0Pd/NpG4-M	8 300 / 7 500	8 400 / 8 200	5,2 / 3,2	5,0 / 3,9
AZI-CQ10Pd/NpG4-M	10 000 / 8 900	10 000 / 10 000	4,8 / 3,05	4,75 / 3,7
AZI-CQ12Pd/NpG4-M	12 000 / 11 600	12 000 / 12 000	4,6 / 3,15	4,95 / 3,8
AZI-CQ14Pd/NpG4-M	14 000 / 12 800	14 000 / 14 000	4,3 / 2,95	4,7 / 3,7
AZI-CQ16Pd/NpG4-M	15 500 / 14 000	15 500 / 15 000	4,4 / 2,85	4,7 / 3,75

