

# Sensira FTXF

Zidni klima-uređaj



## Karakteristike i funkcije

Učinkovitost	Rad	Pročišćavanje zraka	Upravljanje i određivanje rasporeda	Ostalo
	  		  opcija	  

Energetska učinkovitost		FTXF + RXF	20D + 20D	25D + 25D	35D + 35D	42D + 42D	50D + 50D	60D + 60D	71D + 71D
Rashladni učin	Min./Nom./Max.	kW	1,3/2,0/2,4	1,3/2,5/2,8	1,3/3,3/3,8	1,4/4,2/4,3	1,7/5,0/6,0	1,7/6,0/7,0	2,3/7,1/7,3
Učin grijanja	Min./Nom./Max.	kW	1,3/2,4/3,3	1,3/2,8/3,7	1,3/3,5/4,4	1,4/4,6/5,0	1,7/6,0/7,7	1,7/6,4/8,0	2,3/8,2/9,0
Prijelazna snaga	Hlađenje	Min./Nom./Max.	kW	0,31/0,592/0,72	0,31/0,772/1,05	0,31/1,00/1,40	0,31/1,27/1,50	-1,50/-	-1,85/-
	Grijanje	Min./Nom./Max.	kW	0,25/0,640/0,95	0,25/0,750/1,11	0,25/0,940/1,50	0,25/1,24/1,40	-1,62/-	-1,63/-
Hlađenje	Oznaka energetske učinkovitosti					A++			A
	Učin	Pdesign	kW	2,00	2,50	3,50	4,20	5,00	6,00
	SEER				6,50		6,21	6,15	7,10
Space heating (Average climate)	Godišnja potrošnja energije	kWh/a	108	135	188	226	282	342	483
	Oznaka energetske učinkovitosti					A+			A
	Učin	Pdesign	kW	2,20	2,40	2,60	3,30	4,60	4,80
	SCOP/A			4,11		4,30	4,06		3,81
Godišnja potrošnja energije	kWh/a	749	817	885	1.075	1.585	1.654	2.275	

Tehnički podaci - unutarnja jedinica		FTXF	20D	25D	35D	42D	50D	60D	71D
Dimenzije	Jedinica	Visina x Širina x Dubina	286x770x225				295x990x263		
Filter za zrak	Tip		Uklonjiv/periv						
Razina zvučnog tlaka	Hlađenje	Tih/Niski/Srednji/Visoki	dBA	20/25/33/39	20/26/33/40	20/27/34/43	22/30/36/45	31/34/39/43	33/36/41/45
	Grijanje	Tih/Niski/Srednji/Visoki	dBA	21/28/34/39	21/28/34/40	21/29/35/40	22/28/34/44	30/33/38/42	32/35/40/44

Tehnički podaci - vanjska jedinica		RXF	20D	25D	35D	42D	50D	60D	71D
Dimenzije	Jedinica	Visina x Širina x Dubina	550x658x275				734x870x373		
Razina zvučnog tlaka	Hlađenje	Nom./High	dBA	-46		-48	47/-	49/-	52/-
	Grijanje	Nom./High	dBA	-47		-48	49/-		52/-
Radno područje	Hlađenje	Okolina	Min.~Max.	-10~48					
	Grijanje	Okolina	Min.~Max.	-15~24					
Radna tvar	Tip / GWP / Punjenje	kg / TCO,Eq	R-32/675/0,45/0,30	R-32/675/0,55/0,37	R-32/675/0,75/0,51	R-32/675/0,90/0,61	R-32/675/1,15/0,78		
Dimenzije priključka	Duljina cijevi	VJ - UJ	Max.	20			30		
	Visinska razlika	UJ - VJ	Max.	12			20		
Napajanje	Faza / Preporučeni osigurač (MFA)	A	1~ / 16			1~ / 20			

Provjerite objašnjenja karakteristika i funkcija na stranici 39.

