


# Sensira FTXC

Zidni klima-uređaj



## Karakteristike i funkcije



Energetska učinkovitost		FTXC + RXC	20C + 20C	25C + 25C	35C + 35C	50C + 50C	60C + 60C	71C + 71C
Rashladni učin	Min./Rated/Max.	kW	1,3/2,0/3,0	1,3/2,56/3,0	1,3/3,5/4,0	1,4/5,1/6,2	1,8/6,23/7,0	2,3/7,1/7,3
Učin grijanja	Min./Rated/Max.	kW	1,3/2,5/4,0	1,3/2,84/4,0	1,3/4,0/4,8	1,36/5,62/6,6	1,48/6,4/8,0	2,3/7,1/7,3
Hlađenje	Oznaka energetske učinkovitosti				A <sup>++</sup>			A
	Učin Pdesign	kW	2,08	2,57	3,44	5,08	6,21	6,96
	SEER		6,89	6,84	6,87	6,45	6,40	5,30
	Godišnja potrošnja energije	kWh/a	106	132	175	276	340	459
Grijanje (srednja klimatska zona)	Oznaka energetske učinkovitosti				A <sup>+</sup>			A
	Učin Pdesign	kW	1,87	2,23	2,24	3,90	4,10	6,35
	SCOP/A		4,40	4,45	4,28	4,42	4,24	3,81
	Godišnja potrošnja energije	kWh/a	594	700	732	1.236	1.354	2.334

Tehnički podaci - unutarnja jedinica				FTXC	20C	25C	35C	50C	60C	71C
Dimenzije	Jedinica	Visina x Širina x Dubina	mm		288x770x234			297x990x273		
Filter za zrak	Tip				Uklonjiv/periv					
Razina zvučnog tlaka	Hlađenje	Tihi/Niski/Srednji/Visoki	dBA		20/26/33/38		21/26/34/39	29/33/39/45	30/38/42/46	
Tehnički podaci - vanjska jedinica				RXC	20C	25C	35C	50C	60C	71C
Dimenzije	Jedinica	Visina x Širina x Dubina	mm		550x658x273			615x845x300		695x930x350
Razina zvučnog tlaka	Hlađenje	Visoki	dBA		45		46	51	54	
Radno područje	Hlađenje	Okolina	Min.-Max.	°CDB	10~46			-10~46		
		Okolina	Min.-Max.	°CDB				-15~24		
Radna tvar	Tip / GWP / Punjenje		kg/TCO <sub>Eq</sub>		R-32/675/0,550/0,371		R-32/675/0,750/0,506	R-32/675/1,00/0,675	R-32/675/1,10/0,743	R-32/675/1,15/0,776
Dimenzije priključka	Duljina cijevi	VJ - UJ	Max.	m	20			30		
	Sustav razlika	Sustav UJ - VJ	Prednapunjeno	m				8		
	Visinska razlika	UJ - VJ	Max.	m	15			20		
Napajanje	Faza / Preporučeni osigurač (MFA)		A		1~ /16					

Provjerite objašnjenja karakteristika i funkcija na stranici 39.

