

Model			GDN20BE-K5EBA1A
Product Code			CK051037701
Power Supply	Rated Voltage	V~	220-240
	Rated Frequency	Hz	50
	Phases		1
Rated Dehumidification Capacity		L/h	0.5
Power Input		W	350
Current Input		A	1.8
Set Humidity Range		%	30-80
Air Flow Volume(H/M/L)		m ³ /h	170/-/145
Fan Motor Speed		r/min	960/840
Fan Motor Power Output		W	5
Fan Motor RLA		A	0.118
Fan Motor Capacitor		μF	1
Fan Type			Centrifugal
Fan Diameter Length(DXL)		mm	Φ178.5X76.5
Throttling Method			Capillary
Fuse Current		A	3.15
Sound Pressure Level(H/M/L)		dB (A)	39/-/37
Sound Power Level(H/M/L)		dB (A)	53/-/-
Climate Type			T1
Isolation			I
Moisture Protection			IPX0
Permissible Excessive Operating Pressure for the Discharge Side		MPa	3
Permissible Excessive Operating Pressure for the Suction Side		MPa	1.5
Dimension (WXHXD)		mm	352X482X240
Dimension of Carton Box(LXWXH)		mm	389X283X510
Dimension of Package(LXWXH)		mm	392X286X525
Application Area		m ²	30~36
Net Weight		kg	15.5
Gross Weight		kg	17
Refrigerant			R290
Refrigerant Charge		kg	0.08
Bucket Capacity		L	2.6/3.0
Control Type			Electronic
Evaporator	Evaporator Form		Aluminum Fin-copper Tube
	Evaporator Pipe Diameter	mm	Φ7
	Evaporator Row-fin Gap	mm	2-1.4
	Evaporator Coil Length (LXDXW)	mm	238X25.4X190.5
Condenser	Condenser Form		Aluminum Fin-copper Tube
	Condenser Pipe Diameter	mm	Φ5
	Condenser Rows-fin Gap	mm	2-1.4
	Condenser Coil Length (LXDXW)	mm	238X22.8X190.5
Compressor	Compressor Manufacturer		Sichuan Danfu Environment Technology Co.,Ltd
	Compressor Model		DFR60HF
	Compressor Type		Reciprocating
	Compressor Power Input	W	318
	Compressor Overload Protector		HPA-110
	Compressor LRA.	A	11.49
Compressor RLA	A	1.8	

The above data is subject to change without notice; please refer to the nameplate of the unit.