R410 MULTI SPLIT





R410A

EUROVENT CERTIFIED PERFORMANCE www.eurovent-certification.com

LG participates in the ECP programme for EUROVENT AC program. Check ongoing validity of certification : www.eurovent-certification.com

OUTDOOR				FM40AH.U34
Compressor	Type		-	Scroll
Capacity**	Cooling	Min. / Nom. / Max.	kW	2.8 / 12.3 / 15.4
	Heating	Min. / Nom. / Max.	kW	3.1 / 13.5 / 16.2
Low Temperature Capacity	Heating	Max.	kW	12.5
Power Input**	Cooling	Min. / Nom. / Max.	kW	0.82 / 2.42 / 4.90
	Heating	Min. / Nom. / Max.	kW	0.89 / 2.87 / 5.10
Running Current	Cooling	Min. / Nom. / Max.	A	3.7 / 11.0 / 22.2
	Heating	Min. / Nom. / Max.	A	4.0 / 13.0 / 23.1
EER				5.08
COP				4.70
SEER				7.40
SCOP				4.20
Pdesign (@-10°C)			kW	8.6
Seasonal Energy Label (A++ to E Scale)	Cooling / Heating		-	- / -
Annual Energy Consumption	Cooling / Heating		kWh	981 / 2,867
Air Flow Rate		Nom.	m^3/min x No.	110
Sound Pressure Level*	Cooling	Nom.	dB(A)	51
	Heating	Nom.	dB(A)	53
Sound Power Level	Cooling	Max.	dB(A)	69
	Heating	Max.	dB(A)	70
Dimensions		W x H x D	mm	950 x 1,380 x 330
Net Weight			kg	87
Refrigerant	Type		-	R410A
	Charge		kg	4.2
	Additional Charging Volume		g/m	20
	GWP (Global Warming Potential)		-	2,087.5
	t-CO_2eq		-	8.768
Operation Range (Outdoor)	Cooling	Min. / Max.	°C DB	-10 / 48
	Heating	Min. / Max.	°C WB	-25 / 18
Power Supply			Ø / V / Hz	1 / 220 - 240 / 50
Power Supply Cable			No. x mm^2	3C x 4.0
Transmission Cable	ODU~BD		No. x mm^2	4C x 1.25
	BD-IDU		No. x mm^2	4C x 0.75
Circuit Breaker			A	40
Max Piping Length	Total Piping (Main+Total Branch)		m	125
	Main Piping		m	55
	Total Branch Piping		m	70
	Each Branch Piping		m	15
Piping Elevation Difference	IDU~ODU	Max.	m	30
	IDU~IDU	Max.	m	15
Piping Connections	Liquid		mm (inch) x No.	Ø 9.52 x 1
	Gas		mm (inch) x No.	Ø 19.05 x 1

* : Sound Pressure is not a value declared on Eurovent Program.
** : See page "Combination Table".
Note : 1. Capacities are based on the following conditions:
Cooling : - Indoor Temperature 27°C (80.6°F) DB / 19°C (66.2°F) WB - Outdoor Temperature 35°C (95°F) DB / 24°C (75.2°F) WB
Heating : - Indoor Temperature 20°C (68°F) DB / 15°C (59°F) WB - Outdoor Temperature 7°C (44.6°F) DB / 6°C (42.8°F) WB
Piping Length - Interconnecting Piping Length 7.5m - Level Difference of Zero.
2. Due to our policy of innovation some specifications may be changed without notification.
3. At least two indoor units should be connected.
4. Minimum combination capacity rate should be more than 40%.
5. This product contains fluorinated greenhouse gases. (R410A)
※ Based on our policy for the products improvements, specification, design and features are subject to change without any prior notice.
※ Specifications may vary by each model or IDU / ODU combination.



R410A

EUROVENT CERTIFIED PERFORMANCE www.eurovent-certification.com

LG participates in the ECP programme for EUROVENT AC program. Check ongoing validity of certification : www.eurovent-certification.com

OUTDOOR				FM48AH.U34	FM56AH.U34
Compressor	Type		-	Scroll	Scroll
Capacity**	Cooling	Min. / Nom. / Max.	kW	3.3 / 14.1 / 17.0	4.0 / 15.5 / 18.5
	Heating	Min. / Nom. / Max.	kW	3.7 / 16.0 / 17.3	4.5 / 17.4 / 18.8
Low Temperature Capacity	Heating	Max.	kW	14.5	15.5
Power Input**	Cooling	Min. / Nom. / Max.	kW	0.96 / 3.12 / 5.30	1.18 / 3.87 / 5.60
	Heating	Min. / Nom. / Max.	kW	1.06 / 3.76 / 5.40	1.29 / 4.34 / 5.80
Running Current	Cooling	Min. / Nom. / Max.	A	4.4 / 14.1 / 24.0	5.3 / 17.5 / 25.4
	Heating	Min. / Nom. / Max.	A	4.8 / 17.0 / 24.5	5.9 / 19.7 / 26.3
EER				4.51	4.01
COP				4.25	4.01
SEER				7.20	6.90
SCOP				4.20	4.20
Pdesign(@-10°C)			kW	9.5	9.5
Seasonal Energy Label (A++ to E Scale)	Cooling / Heating		-	- / -	- / -
Annual Energy Consumption	Cooling / Heating		kWh	1,167 / 3,167	1,348 / 3,167
Air Flow Rate		Nom.	m^3/min x No.	110	110
Sound Pressure Level*	Cooling	Nom.	dB(A)	53	53
	Heating	Nom.	dB(A)	55	55
Sound Power Level	Cooling	Max.	dB(A)	71	73
	Heating	Max.	dB(A)	72	74
Dimensions		W x H x D	mm	950 x 1,380 x 330	950 x 1,380 x 330
Net Weight			kg	87	87
Refrigerant	Type		-	R410A	R410A
	Charge		kg	4.2	4.2
	Additional Charging Volume		g/m	20	20
	GWP (Global Warming Potential)		-	2,087.5	2,087.5
	t-CO_2eq		-	8.768	8.768
Operation Range (Outdoor)	Cooling	Min. / Max.	°C DB	-10 / 48	-10 / 48
	Heating	Min. / Max.	°C WB	-25 / 18	-25 / 18
Power Supply			Ø / V / Hz	1 / 220 - 240 / 50	1 / 220 - 240 / 50
Power Supply Cable			No. x mm^2	3C x 4.0	3C x 4.0
Transmission Cable	ODU-BD		No. x mm^2	4C x 1.25	4C x 1.25
	BD-IDU		No. x mm^2	4C x 0.75	4C x 0.75
Circuit Breaker			A	40	40
Max Piping Length	Total Piping (Main+Total Branch)		m	135	145
	Main Piping		m	55	55
	Total Branch Piping		m	80	90
	Each Branch Piping		m	15	15
Piping Elevation Difference	IDU-ODU	Max.	m	30	30
	IDU-IDU	Max.	m	15	15
Piping Connections	Liquid		mm (inch) x No.	Ø 9.52 x 1	Ø 9.52 x 1
	Gas		mm (inch) x No.	Ø 19.05 x 1	Ø 19.05 x 1

* : Sound Pressure is not a value declared on Eurovent Program.
** : See page "Combination Table".
Note : 1. Capacities are based on the following conditions :
Cooling : - Indoor Temperature 27°C (80.6°F) DB / 19°C (66.2°F) WB - Outdoor Temperature 35°C (95°F) DB / 24°C (75.2°F) WB
Heating : - Indoor Temperature 20°C (68°F) DB / 15°C (59°F) WB - Outdoor Temperature 7°C (44.6°F) DB / 6°C (42.8°F) WB
Piping Length - Interconnecting Piping Length 7.5m - Level Difference of Zero.
2. Due to our policy of innovation some specifications may be changed without notification.
3. At least two indoor units should be connected.
4. Minimum combination capacity rate should be more than 40%.
5. This product contains fluorinated greenhouse gases. (R410A)
※ Based on our policy for the products improvements, specification, design and features are subject to change without any prior notice.
※ Specifications may vary by each model or IDU / ODU combination.



R410A

3Phase

EUROVENT CERTIFIED PERFORMANCE www.eurovent-certification.com

LG participates in the ECP programme for EUROVENT AC program. Check ongoing validity of certification : www.eurovent-certification.com

OUTDOOR				FM41AH.U34	FM49AH.U34	FM57AH.U34
Compressor	Type		-	Scroll	Scroll	Scroll
Capacity**	Cooling	Min. / Nom. / Max.	kW	2.8 / 12.3 / 15.4	3.3 / 14.1 / 17.0	4.0 / 15.5 / 18.5
	Heating	Min. / Nom. / Max.	kW	3.1 / 13.5 / 16.2	3.7 / 16.0 / 17.3	4.5 / 17.4 / 18.8
Low Temperature Capacity	Heating	Max.	kW	12.5	14.5	15.5
Power Input**	Cooling	Min. / Nom. / Max.	kW	0.82 / 2.42 / 4.90	0.96 / 3.12 / 5.30	1.18 / 3.87 / 5.60
	Heating	Min. / Nom. / Max.	kW	0.89 / 2.87 / 5.10	1.06 / 3.76 / 5.40	1.29 / 4.34 / 5.80
Running Current	Cooling	Min. / Nom. / Max.	A	1.2 / 3.6 / 7.4	1.4 / 4.7 / 8.0	1.8 / 5.8 / 8.4
	Heating	Min. / Nom. / Max.	A	1.3 / 4.3 / 7.7	1.6 / 5.7 / 8.1	1.9 / 6.5 / 8.7
EER				5.08	4.51	4.01
COP				4.70	4.25	4.01
SEER				7.40	7.20	6.90
SCOP				4.20	4.20	4.20
Pdesign(@-10°C)			kW	8.6	9.5	9.5
Seasonal Energy Label (A++ to E Scale)	Cooling / Heating		-	- / -	- / -	- / -
Annual Energy Consumption	Cooling / Heating		kWh	981 / 2,867	1,167 / 3,167	1,348 / 3,167
Air Flow Rate		Nom.	m^3/min x No.	110	110	110
Sound Pressure Level*	Cooling	Nom.	dB(A)	51	53	53
	Heating	Nom.	dB(A)	53	55	55
Sound Power Level	Cooling	Max.	dB(A)	69	71	73
	Heating	Max.	dB(A)	70	72	74
Dimensions		W x H x D	mm	950 x 1,380 x 330	950 x 1,380 x 330	950 x 1,380 x 330
Net Weight			kg	87	87	87
Refrigerant	Type		-	R410A	R410A	R410A
	Charge		kg	4.2	4.2	4.2
	Additional Charging Volume		g/m	20	20	20
	GWP (Global Warming Potential)		-	2,087.5	2,087.5	2,087.5
	t-CO_2eq		-	8.768	8.768	8.768
Operation Range (Outdoor)	Cooling	Min. / Max.	°C DB	-10 / 48	-10 / 48	-10 / 48
	Heating	Min. / Max.	°C WB	-25 / 18	-25 / 18	-25 / 18
Power Supply			Ø / V / Hz	3 / 380 - 415 / 50	3 / 380 - 415 / 50	3 / 380 - 415 / 50
Power Supply Cable			No. x mm^2	5C x 2.5	5C x 2.5	5C x 2.5
Transmission Cable	ODU-BD		No. x mm^2	4C x 1.25	4C x 1.25	4C x 1.25
	BD-IDU		No. x mm^2	4C x 0.75	4C x 0.75	4C x 0.75
Circuit Breaker			A	20	20	20
Max Piping Length	Total Piping (Main+Total Branch)		m	125	135	145
	Main Piping		m	55	55	55
	Total Branch Piping		m	70	80	90
	Each Branch Piping		m	15	15	15
Piping Elevation Difference	IDU-ODU	Max.	m	30	30	30
	IDU-IDU	Max.	m	15	15	15
Piping Connections	Liquid		mm (inch) x No.	Ø 9.52 x 1	Ø 9.52 x 1	Ø 9.52 x 1
	Gas		mm (inch) x No.	Ø 19.05 x 1	Ø 19.05 x 1	Ø 19.05 x 1

* : Sound Pressure is not a value declared on Eurovent Program.
** : See page "Combination Table".
Note : 1. Capacities are based on the following conditions :
Cooling : - Indoor Temperature 27°C (80.6°F) DB / 19°C (66.2°F) WB - Outdoor Temperature 35°C (95°F) DB / 24°C (75.2°F) WB
Heating : - Indoor Temperature 20°C (68°F) DB / 15°C (59°F) WB - Outdoor Temperature 7°C (44.6°F) DB / 6°C (42.8°F) WB
Piping Length - Interconnecting Piping Length 7.5m - Level Difference of Zero.
2. Due to our policy of innovation some specifications may be changed without notification.
3. At least two indoor units should be connected.
4. Minimum combination capacity rate should be more than 40%.
5. This product contains fluorinated greenhouse gases. (R410A)
※ Based on our policy for the products improvements, specification, design and features are subject to change without any prior notice.
※ Specifications may vary by each model or IDU / ODU combination.